ROYAUME DE BELGIQUE

MINISTERE DES AFFAIRES ECONOMIQUES ADMINISTRATION DE LA POLITIQUE COMMERCIALE.

REC'D 2 3 AUG 2004

WIPO PCT

Il est certifié que les annexes à la présente sont la copie fidèle de documents que détient l'Office de la Propriété Industrielle.


Bruxelles, le -9. -8 - 2004

Pour le Conseiller de l'Office de la Propriété industrielle

Le fonctionnaire délégué,

Genseiller adjoint

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)



PCT

REQUEST

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

- For receiving Office use only -

PC T / BE 0 3 / 00 16 2

International Application No.

26 SEP 2003 International Filing Date

26 -09- 2003

RO/SE - INTERNATIONAL APPLICATION

Name of receiving Office and "PCT International Application"

Applicant's or agent's file reference (if desired) (12 characters maximum) ORPC 135.435/ MJ

(ly desired) (12 cha	racters maximum) ORFC 135.435/ IVIJ			
Box No. I TITLE OF INVENTION				
Low-trans fats for confectionery fat compositions				
Box No. II APPLICANT This person is also inventor .				
Name and address: (Family name followed by given name; for a legal entity, full official designat The address must include postal code and name of country. The country of the address indicated in Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)	tion. this			
FUJI OIL EUROPE	Facsimile No.			
Kuhlmannlaan 36	Televisia N			
B-9042 Gent	Teleprinter No.			
Belgium	A-11-11-11-11-11-11-11-11-11-11-11-11-11			
	Applicant's registration No. with the Office			
State (that is, country) of nationality: State (that is, country) State (that is, country)	untry) of residence:			
This person is applicant all designated for the purposes of: all designated all designated States except the United States of America	the United States of America only the States indicated in the Supplemental Box			
Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR				
Name and address: (Family name followed by given name; for a legal entity, full official designa The address must include postal code and name of country. The country of the address indicated in	tion. This person is:			
Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)	applicant only			
CLEENEWERCK, Bernard				
Rozenlaan 35	applicant and inventor			
B-9185 Wachtebeke	inventor only (If this check-box is marked, do not fill in below.)			
Belgium				
	Applicant's registration No. with the Office			
State (that is, country) of nationality: BE State (that is, country) BE	untry) of residence:			
This person is applicant all designated all designated States except for the purposes of:	the United States the States indicated in the Supplemental Box			
Further applicants and/or (further) inventors are indicated on a continuation sh	reet.			
Box No. IV AGENT OR COMMON REPRESENTATIVE; OR ADDRESS I	FOR CORRESPONDENCE			
The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent common representative			
Name and address: (Family name followed by given name; for a legal entity, full official designa. The address must include postal code and name of country.)	tion. Telephone No. +32 2 535 99 11			
LUYS, Marie-José	Facsimile No.			
Gevers & Vander Haeghen	+ 32 2 535 99 00			
Intellectual Property House	Teleprinter No.			
Brussels Airport Business Park				
Holidaystraat 5	Agent's registration No. with the Office			
B-1831 Diegem (Belgium)				
Address for correspondence: Mark this check-box where no agent or commo space above is used instead to indicate a special address to which correspondence:	on representative is/has been appointed and the nee should be sent.			

Form PCT/RO/101 (first sheet) (March 2001; reprint July 2003)

See Notes to the request form

Precautionary Designation Statement: In addition to the designations made above, the applicant also makes under Rule 4.9(b) all other designations which would be permitted under the PCT except any designation(s) indicated in the Supplemental Box as being excluded from the scope of this statement. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit. (Confirmation (including fees) must reach the receiving Office within the 15-month time limit.)

Supplemental Box

If the Supplemental Box is not used, this sheet should not be included in the request.

- 1. If, in any of the Boxes, except Boxes Nos. VIII(i) to (v) for which a special continuation box is provided, the space is insufficient to furnish all the information: in such case, write "Continuation of Box No..." (indicate the number of the Box) and furnish the information in the same manner as required according to the captions of the Box in which the space was insufficient, in particular:
- (i) if more than two persons are to be indicated as applicants and/or inventors and no "continuation sheet" is available: in such case, write "Continuation of Box No. III" and indicate for each additional person the same type of information as required in Box No. III. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below;
- (ii) if, in Box No. II or in any of the sub-boxes of Box No. III, the indication "the States indicated in the Supplemental Box" is checked: in such case, write "Continuation of Box No. II" or "Continuation of Box No. III" or "Continuation of Boxes No. III and No. III" (as the case may be), indicate the name of the applicant(s) involved and, next to (each) such name, the State(s) (and/or, where applicable, ARIPO, Eurasian, European or OAPI patent) for the purposes of which the named person is applicant;
- (iii) if, in Box No. II or in any of the sub-boxes of Box No. III, the inventor or the inventor/applicant is not inventor for the purposes of all designated States or for the purposes of the United States of America: in such case, write "Continuation of Box No. II" or "Continuation of Box No. II" or "Continuation of Boxes No. II and No. III" (as the case may be), indicate the name of the inventor(s) and, next to (each) such name, the State(s) (and/or, where applicable, ARIPO, Eurasian, European or OAPI patent) for the purposes of which the named person is inventor;
- (iv) if, in addition to the agent(s) indicated in Box No. IV, there are further agents: in such case, write "Continuation of Box No. IV" and indicate for each further agent the same type of information as required in Box No. IV;
- (v) if, in Box No. V, the name of any State (or OAPI) is accompanied by the indication "patent of addition," or "certificate of addition," or if, in Box No. V, the name of the United States of America is accompanied by an indication "continuation" or "continuation-in-part": in such case, write "Continuation of Box No. V" and the name of each State involved (or OAPI), and after the name of each such State (or OAPI), the number of the parent title or parent application and the date of grant of the parent title or filing of the parent application;
- (vi) if, in Box No. VI, there are more than five earlier applications whose priority is claimed: in such case, write "Continuation of Box No. VI" and indicate for each additional earlier application the same type of information as required in Box No. VI.
- If, with regard to the precautionary designation statement contained in Box No. V, the applicant wishes to exclude any State(s) from the scope of that statement: in such case, write "Designation(s) excluded from precautionary designation statement" and indicate the name or two-letter code of each State so excluded.

CONTINUATION OF BOX IV ADDITIONAL AGENTS:

Claeys Pierre, Gevers Florent, Gevers François, Gevers Jacques, Grisar Daniel, Luys Marie-José, Pieraerts Jacques, Quintelier Claude, Rossini -de Taxis du Poët Dominique, Schmitz Yvon, Van Reet Joseph, Vosswinkel Philippe

Professional address:

Gevers & Vander Haeghen Intellectual Property House Brussels Airport Business Park Holidaystraat 5 B-1831 Diegem Belgium

Telephone N°: +32 2 535 99 11 Fax N°: +32 2 535 99 00

process of the 10110		_			
	wing earlier application(s) is here	by claimed:			
Filing date of earlier application	Number of earlier application	Where earlier application		is:	
(day/month/year)	application	national application: country or Member of WTO	regional application:*	international application	
item (I)			Brown Girler	receiving Office	
item (2)				, , , , , , , , , , , , , , , , , , , ,	
item (3)					
	•				
item (4)		·			
item (5)					
Further priority elei-	ns are indicated in the Supplement			•	
Box No. VII INTERNA		***********	***************		
Choice of International S nternational search, indical SA /	earching Authority (ISA) (if two the Authority chosen; the two-learlier search; reference to the thority):	HORITY o or more International Sea letter code may be used):	arching Authorities are co	ompetent to carry out the	
Choice of International S International search, indica	searching Authority (ISA) (if tw te the Authority chosen; the two-l	HORITY o or more International Sea etter code may be used): at search (if an earlier sear	arching Authorities are co	ompetent to carry out the	
Choice of International S nternational search, indical SA /	searching Authority (ISA) (if twate the Authority chosen; the two-learlier search; reference to the thority): Number	HORITY o or more International Sea etter code may be used): at search (if an earlier sear	arching Authorities are co	ompetent to carry out the	
Choice of International S nternational search, indical SA / Request to use results of onternational Searching Autoritional Search Sea	cearching Authority (ISA) (if two the the Authority chosen; the two-learlier search; reference to the thority): Number	HORITY o or more International Sea etter code may be used): at search (if an earlier sear Country	arching Authorities are co control of the control o	ompetent to carry out the by or requested from the Number of	
Choice of International S nternational search, indical SA / Request to use results of onternational Searching Auto oate (day/month/year) ox No. VIII DECLARA the following declarational	cearching Authority (ISA) (if two-lete the Authority chosen; the two-lete the Authority chosen; the two-lete the thority): Number	HORITY o or more International Sea etter code may be used): at search (if an earlier sear Country III (i) to (v) (mark the appler of each type of declaration	arching Authorities are co control of the control o	ompetent to carry out the by or requested from the	
Choice of International S International search, indical SA / Request to use results of othernational Searching Autoritional Searching Autoritional Searching Autoritional Searching Autoritional Searching Autoritional Search No. VIII DECLARA The following declarations are check-boxes below and indicated.	cearching Authority (ISA) (if twente the Authority chosen; the two-learlier search; reference to the thority): Number ATIONS Searce contained in Boxes Nos. Vicate in the right column the number that the right column the right c	HORITY o or more International Sealetter code may be used): at search (if an earlier sear Country III (i) to (v) (mark the applier of each type of declaration of the inventor	arching Authorities are control of the control of t	ompetent to carry out the by or requested from the Number of	
Choice of International S nternational search, indical SA / Request to use results of onternational Searching Autorities ate (day/month/year) OX No. VIII DECLARA the following declarations seck-boxes below and indical Box No. VIII (i)	cearching Authority (ISA) (if two the the Authority chosen; the two-learlier search; reference to the thority): Number ATIONS So are contained in Boxes Nos. Vicate in the right column the number column the number of the column as to the identity of the column as to the applicant of the applicant of the search of the applicant of the search of the s	HORITY o or more International Sealetter code may be used): at search (if an earlier sear Country III (i) to (v) (mark the applier of each type of declaration of the inventor at's entitlement, as at the inted a patent	arching Authorities are control of the control of t	ompetent to carry out the by or requested from the Number of	
Choice of International Senternational Search, indicased SA /	cearching Authority (ISA) (if two the the Authority chosen; the two-learning search; reference to the thority): Number ATIONS So are contained in Boxes Nos. Vicate in the right column the number Declaration as to the identity of Declaration as to the applicant date, to apply for and be gran Declaration as to the applicant date, to apply for and be gran Declaration as to the applicant date, to apply for and be gran Declaration as to the applicant date, to apply for and be gran Declaration as to the applicant date.	o or more International Sealetter code may be used): at search (if an earlier sear Country III (i) to (v) (mark the applier of each type of declaration of the inventor at's entitlement, as at the inted a patent at's entitlement, as at the inted a patent	arching Authorities are control of the control of t	ompetent to carry out the by or requested from the Number of	

Box No. IX CHECK LIST; LANGUAGE OF FILING
This international application contains: (a) in paper form, the following number of sheets: request (including deciaration sheets) : 5 description (excluding sequence listings and/or tables related thereto) : 23 abstract : 1 drawings : 3 Sub-total number of sheets : 32 sequence listings (for both, actual number of sheets if filed in paper form, whether or not also filed in computer readable form; see (c) below) Total number of sheets : 30 Tot
(ii) sequence listings (ii) sequence listings (iii) sequence listings (ii) sequence listings (iii) sequence listings (ivaliate type and number of carriers)
Figure of the drawings which should accompany the abstract: Box No. X SIGNATURE OF ARRIVATION AND ACCOUNTS A CONTRACT AND ACCOUNTS ASSOCIATED ACCOUNTS ASSOCIATED AND ACCOUNT
Box No. X SIGNATURE OF APPLICANT, AGENT OR COMMON REPRESENTATIVE Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request) Antwerp, September 26, 2003 LUYS, Marie-José
1. Date of actual receipt of the purported international application: For receiving Office use only 2 6 SEP 2003 2. Drawings: Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application:
4. Date of timely receipt of the required corrections under PCT Article 11(2):
5. International Searching Authority (if two or more are competent): ISA / 6. Transmittal of search copy delayed until search fee is paid
For International Bureau use only Date of receipt of the record copy by the International Bureau:

Low-trans fats for confectionery fat compositions.

The present invention relates to a process for producing a fat composition suitable for use as confectionery fat, as described in the preamble of the first claim.

5

10

The present invention also relates to the fat composition as such and to the use of the fat composition in several confectionery applications.

1. BACKGROUND OF THE INVENTION.

1.1. Filling fats and cream fats.

A first important application area of confectionery fats is the so-called filling and cream fats. Filling and cream fats are used for the production of for example soft centres for pralines or confectionery bars or for creams used in or on biscuits or wafers. To be suitable for use as a cream and/or filling fat, it is important that the fat has specific properties such as good melting properties in the mouth, good creaminess as well as a stable crystal structure. Several types of fats capable of providing these properties are known in the art.

20

25

30

15

A first class of fats suitable for use as filling and/or cream fats includes the so-called lauric fats. The lauric fats are derived from coconut oil or palm kernel oil and contain a high amount of lauric and myristic acid. By subjecting these lauric fats to a fractionation and/or a hydrogenation reaction, a lauric fat with a steep SFC-profile can be obtained, i.e. a lauric fat of which the solid fat content (SFC) as a function of temperature is high at room temperature, whereas at body temperature the solid fat content is low and the fat is completely molten. This sharp transition from solid to liquid gives a cool sensation in the mouth. Besides showing a steep SFC-profile, lauric fats show a quick solidification, which is an advantage when used in fillings and creams. Although they are frequently applied in practise, lauric type fats have a number of disadvantages, a major disadvantage being the risk to saponification of the lauric acid upon ageing, involving the occurrence of a bad taste. Another disadvantage

CONFIRMATION COPY

of lauric fats is their high saturated fatty acid content, often over 80%, which is considered an important nutritional disadvantage.

A second class of cool melting filling and cream fats is based on fractionated palm oil. Palm oil as such shows a rather flat SFC-curve with a SFC at 20°C of only 25 %, while at 35°C the SFC is 6%. By subjecting palm oil to a fractionation process a product with steeper SFC-profile can be obtained. Fractionation of palm oil is carried out by cooling palm oil to a certain temperature, until a liquid phase is obtained containing triglycerides with a the lower melting point, and a solid phase containing triglycerides with a higher melting point. Reduction of the tailing effect of the SFC curve is achieved by removing the high melting part, which mainly consists of trisaturated triglycerides like tripalmitine. Fats associated with this tailing cause a waxy feeling in the mouth upon eating. In a next stage, through removal of the part with the lower melting temperature, which mainly comprises tri- or di-unsaturated triglycerides like tri-oleine or 1-palmitic 2-3-oleic triglycerides, the SFC at room temperature is increased. The fraction remaining after removal of the higher and lower melting part of the palm oil is commonly indicated by the name PMF (palm mid fraction).

The most important advantages of PMF-based filling and cream fats are their non-lauric nature, the lower content of saturated fatty acids, the fresh melting sensation upon eating and the fact that PMF is a non-hydrogenated fat. A major disadvantage of PMF however resides in the rather long and laborious fractionation process involved, together with the rather low production yields, which renders the product expensive: starting from palm oil with most fractionation processes, only 25-30 % of PMF is obtained. The yields of hard PMF obtained via double fractionation are even lower. A further disadvantage is the slow solidification rate of PMF, which necessitates in the confectionery plant the use of devices with high cooling capacities. Besides this, PMF based fats show a risk to re-crystallisation, causing "graininess" of the final product when stored for some time, in particular in case no tempering is applied.

A third type of filling and cream fats is based on hydrogenated liquid oils or hydrogenated olein fractions. This type of fat compositions is characterised by a good creaminess and good melting properties, although they may show less cooling sensation in the mouth, which is typical for the two previous types of fat compositions. Products containing these fats show a

quick solidification and a stable texture. In addition to this, hydrogenated liquid oils and olein fractions are less expensive compared to the former products since their raw materials are largely available and their processing is less complicated as compared to fractionation of palm oil.

5

10

The presence of trans fatty acids entails the advantage of improving the crystallisation rate of the fat composition containing them. However the often too high trans fatty acids content of hydrogenated liquid oils and olein fractions, has become a health concern, the importance of which is increasing. Although trans fatty acids are unsaturated fatty acids, they have undesirable effects comparable to or even worse than saturated fatty acids (SFA). As a consequence, there is an interest to not only control the SFA level of a fat composition, but to control also the sum of the TFA and SFA levels. If it is envisaged to obtain products with steep SFC-profiles, the hydrogenation reaction is mostly carried out in the presence of a trans-specific catalyst, for example Spoisoned Ni-catalysts.

15

20

From the above, it will become clear that there is a need to a fat composition suitable for use as a confectionery fat and to a method for producing such a fat composition. In particular there is a need to a fat composition which preferably is non-lauric, which is characterised by a good melting in the mouth without involving waxiness, which shows a sufficiently high crystallisation rate and has an interesting nutritional profile, which means that the composition should have a low content of both saturated and trans fatty acids. Furthermore it is of importance that the fat composition shows a low risk to recrystallisation or fat blooming when used for instance in combination with enrobed chocolate.

25

30

From EP-A-547.651 it is known to use in filling fats a blend of (i) a non lauric fat, in particular a mid-fraction obtained from wet fractionation of hardened soybean oil containing fat mixtures; and (ii) a liquid, trans-hardened high stability oil, in particular olein fractions obtainable from wet fractionation of hardened soybean oil containing fat mixtures. Thereto, combinations of soybeanoil and palm oil olein are subjected to a trans-selective hydrogenation reaction. In the wet fractionation preferably aceton is used as a solvent, for the trans-selective hydrogenation a sulphided Ni-catalyst is found very suitable. The blends of mid-fractions and olein-fractions of such trans-

hydrogenated combinations give filling fats with a minimised waxiness, a steep melting curve and, a steep SFC-profile with N20 > 40 % and N30 < 8 %, and good mouthfeel. However, the trans fatty acid content of these fat composition ranges from 35 to 45%, which is too high.

Patent application PCT/BE02/00045 discloses a process for the production of a fat composition suitable for use as confectionery fat in confectionery fillings and creams, showing a steep SFC profile but simultaneously having a low trans fatty acid content. According to the process of PCT/BE02/00045, a fat composition containing palm oil or a palm oil fraction, the fat composition having a specific composition in terms of triglyceride and diglyceride content, is subjected to a catalytic hydrogenation, with the aim of obtaining a first fat the trans and saturated fatty acid content of which is increased to only a limited extent upon hydrogenation. The thus obtained first fat is incorporated in a fat composition. According to PCT/BE02/00045 it is possible to combine the first fat with a second fat with low trans fatty acid content. Suitable fat composition for use as second include for example a soft palm fraction or a liquid oil. Confectionery creams containing the fat composition of PCT/BE02/00045 show a good mouth feel and virtually no graininess.

1.2. Coating fats and hard centre fats.

5

10

15 .

20

25

30

Besides the above discussed use of confectionery fats in fillings and creams, confectionery fats of a harder type know a second important application area, namely in hard centres and in confectionery coatings and tablets. These include the so called hard butters. Hard butters are characterised by a steep SFC-profile: they have a high solid fat content and are hard at room temperature. At body temperature the hard butters melt and their solid fat content becomes negligible. These confectionery fats have a SFC profile that is similar to that of cocoa butter, which is the traditional chocolate fat. Hard centres is understood to designate confectionery centres with a firm texture, that are usually produced by extrusion.

Over the years, three main classes of hard butters have been developed for use in coatings or tablets including (i) lauric cocoa butter substitutes, (ii) cocoa butter equivalents (CBE) containing palm oil fractions combined with so-called wild fats like illipe or shea fat, and (iii) non-lauric cocoa

butter replacers (NL-CBR) based on trans-specific hydrogenated liquid oils or liquid fractions. These three classes of cocoa butter alternatives correspond to the three classes of filling fats described above.

5

10

15

20

25

30

In general fillings and creams will be softer than tablets and coatings. The reasons for the higher softness of fillings and creams resides in the higher fat content of these products as compared to tablets and coatings and in the softer nature of the fats contained therein, i.e. the lower SFC at room temperature. Both for filling and cream fats and for coating fats it is important to have a steep SFC-profile, which means that at room temperature the SFC should be sufficiently high, whereas at body temperature the SFC should be low, in order to avoid a "waxy" mouth feel. This explains the similar approach used in the production of filling/cream fats and the so-called hard butters.

Palm fractions used in the production of CBE are typically obtained by wet fractionation, which gives a PMF of better quality as compared to PMF obtained from dry or detergent fractionation, the wet fractionation process however being the more expensive one. The wet fractionation process guarantees a sharp fractionation, with an efficient removal of low melting triglycerides like POO (P = Palmitic acid; O = Oleic acid) and high melting triglycerides like PPP. The wet fractionation is also an efficient process for removing diglycerides from the palm mid fraction, which are to be avoided in CBE products. It is important to mention here that CBEs differ from non-lauric CBR and lauric cocoa butter substitutes in that they are a tempering type of fat, similar to natural cocoa butter. Tempering is a process step in which a molten chocolate mixture is subjected to a temperature conditioning process. In particular, in the tempering step the molten chocolate mixture is subjected to a process involving cooling and heating, with the aim of stimulating and maximising crystallisation of the fat in a stable crystalline form.

The production of non-lauric CBR is described by W. Soon in "Specialty fats versus Cocoa Butter" page 189-192. According to W. Soon, liquid oils like soybean oil, rapeseed oil and sunflower oil are suitable raw materials for a hydrogenation process, as well as liquid fractions like highly fractionated palm olein (iodine value > 68). However, according to W. Soon, care needs to be taken to carry out the hydrogenation process in such a way that production of trisaturated triglycerides (SSS where S = Saturated) is minimised, as

these have a high melting point and induce waxiness. This result may be achieved through an appropriate selection of the hydrogenation catalyst. In particular, W. Soon advises to carry out the hydrogenation reaction in the presence of a sulphur poisoned nickel catalyst as this promotes the formation of trans-isomers, which give a steep SFC-profile, formation of SSS isomers being minimised. When producing a palm oil based non-lauric CBR, it is advisable to use as a starting material a palm olein the PPP and PPO/POP content of which is as low as possible. PPP is a trisaturated fatty acid naturally present in palm oil. With PPO and POP saturation of one single fatty acid suffices to build trisaturated fatty acids.

10

5

The effect of using a sulphur poisoned Ni-catalyst in a hydrogenation reaction of palm olein in stead of a traditional non trans specific Ni-catalyst on palm olein has been described by H. Mori in "Crystallisation and polymorphism of fats and fatty acids" pg 430-431. According to Mori when using a trans specific catalyst, a confectionary fat with a sharp melting curve is obtained, which is not the case when using conventional hydrogenation catalyst.

15

20

25

US-A-4.205.095 relates to a method for the production of cocoa butter substitutes, according to which a palm mid fraction is subjected to a catalytic hydrogenation reaction in the presence of a nickel, platinum or palladium catalyst. The purpose of the hydrogenation reaction is to extend the possibilities of blending PMF with cacao butter by removing triglycerides containing more than one unsaturated fatty acid (SU₂ and U₃) as much as possible and by converting polyunsaturated hydrocarbon chains of the fatty acids into mono-unsaturated hydrocarbon chains, thereby reducing the iodine value to 38-45, the linoleic acid content to below 2 % and achieving a fat composition with a melting point of between 33-36°C. The cocoa butter substitutes disclosed in US-A-4.205.095 are meant to be used in chocolate products like tablets or coatings.

30

From US-A-3.686.240 a process is known for producing a vegetable fat product suitable for replacing at least part of cocoa butter in chocolate, the properties of the vegetable fat product being similar to those of cocoa butter. According to US-A-3.686.240 this vegetable fat product is obtained by subjecting a palm oil middle melting point fraction (PMF) to a hardening process through hydrogenation, with the aim of producing a fat which upon blending with natural cocoa butter shows full compatibility with cocoa butter,

does not soften or does not get a lower melting point. The full compatibility with cocoa butter implies that the product obtained with this process is a tempering type of fat. It is further explained that the palm mid fraction should be prepared by solvent fractionation using a specific solvent.

5

EP-A-0.536.824 solves the problem of providing a non-temper confectionery fat composition which is free of trans fatty acids. The composition consists of a (i) first fat obtained by double fractionated palm mid fraction obtained by wet fraction, containing more than 70 wt% POP triglycerides, capable of crystallisation in the Beta crystal form, and (ii) a second fat, capable of stabilising Beta prime crystals and comprising triglycerides of the SSO and/or S3-type. An example of the second fat is a PPO-rich fat obtained by enzymatic interesterification, having a PPO content of 65.5 wt. %. As the fat composition of EP-A-0.536.824 does not contain trans fatty acids, the fat composition cannot have been subjected to a partial hydrogenation.

15

20

10

The fat composition of EP-A-536.824 is a non-temper type, which follows from the comparison of the SFC-values at 30°C of the fat composition which has not been subjected to a stabilisation process, with a fat composition that has been subjected to a stabilisation (tempering) step. It is claimed that the ratio of both SFC values should be below 4, preferably below 3, the examples giving fat compositions of which the SFC ratio ranges from 1.7 to 3.2. The application of these fat compositions in confectionery coating recipes containing no cocoa mass, having a cocoabutter/fat blend ratio of 5/95 is demonstrated. In the preparation of the fat compositions of EP 0 536 824, no hydrogenation step is involved.

25

The fat composition obtainable with the process of PCT/BE02/00045, which is low in trans fatty acids, proofed to be very suitable for use in for example hard centres and confectionery coatings and tablets.

1.3. Caramel.

30

A third kind of application of fats in the confectionery area is their use in caramel. Caramel is understood to include both high boiling and soft caramels. Fats give a certain consistency to the caramel, they control chewiness and reduce stickiness. In caramels, traditionally hydrogenated liquid oils such as hydrogenated soybean oil or hydrogenated rapeseed oil are used. In

stead of these oils, lauric fats like hydrogenated palm kernel or hydrogenated coconut oil can be used as well. Because of the too high content of trans fatty acids or saturated fatty acids of the conventionally used hydrogenated oils, there is a need for alternatives having a low trans fatty acid content, which show a melting profile similar to the conventionally used oils and which may be produced at an acceptable cost for this application.

The process of PCT/BE02/00045 proofed to be suitable for the production of fats for use in caramels.

10

15

20

25

30

· 5

2. OBJECT OF THE INVENTION.

It is an object of the present invention to provide a fat composition for use as a confectionery fat, which is characterised by a steep SFC-profile, which has an interesting nutritional profile, i.e. has a low content of trans fatty acids and a sufficiently low content of saturated fatty acids, a high crystallisation rate and which shows a reduced tendency to re-crystallisation or fat blooming.

Another object of this invention is to provide a fat composition which is suitable for use in fillings and in creams, and also in caramel with the aim of replacing therein fats containing high levels of trans fatty acids or saturated fatty acids.

It is a further object of the present invention to provide a fat composition which is suitable for use in confectionery centres, confectionery coatings and tablets, the fat composition being suitable to fully or partially replace fats with a high trans fatty acid content, while maintaining a steep SFC-profile, whereby the confectionery product can be prepared without necessitating tempering step.

Thereby it is important that the fat composition can be prepared starting from a fat which does not require extensive and expensive fractionation processes to render it suitable for use in the above mentioned applications.

3. DESCRIPTION OF THE INVENTION.

It has now been found with the present invention that a fat composition suitable for use as confectionery fat can be obtained by subjecting a starting fat composition to a catalytic hydrogenation reaction as described in the characterising part of the first claim.

The starting fat composition is characterised:

(1) by a glyceride composition with:

amount of di-and triglycerides.

5

10

15

20

25

30

- A S₂U content between 30 and 80 wt. %, preferably between 40 and 70 wt. %, most preferably between 45 and 65 wt. %,
- A SU₂ + U₃ content of below 60 wt. %, preferably between 10 and 50 wt. %, most preferably between 20 and 40 wt. %,
- A S₃ content of below 20 wt. %, preferably less than 15 wt. %, most preferably less than 10 wt. %
- A diglyceride content between 3 and 12 wt. %, the glyceride contents being expressed as wt. % with respect to the total
- (2) in that the starting fat composition contains an amount of an interesterified fat, in particular between 10 to 100 wt. % of interesterified fat, preferably 20 to 80 wt. %, most preferably 30 to 70 wt. %. The amounts of interesterified fat are expressed as wt. % with respect to the total amount of starting fat

The starting fat composition is subjected to a catalytic hydrogenation until a hydrogenated first fat is obtained which is characterised by a trans fatty acid (TFA) content of less than 25 wt. %, preferably less than 20 wt. %, more preferably less than 10 wt. % with respect to the total fat content. The hydrogenated first fat is incorporated in the fat composition. The amount of the first fat incorporated in the fat composition may vary within wide ranges and may even be 100 wt%.

In the above, S means saturated fatty acid with a hydrocarbon chain length of 14-24 carbon atoms, and U means unsaturated fatty acid with a hydrocarbon chain length of 14-24 carbon atoms.

The starting fat composition preferably comprises palm oil or a fraction thereof, obtained by dry fractionation or even detergent fractionation if so desired. The starting fat composition may if so desired however also comprise other fats.

The inventor has now found that the incorporation in the starting fat composition of an amount of interesterified fat and the subjecting of this starting fat composition to a hydrogenation, results in a fat having an improved resistance against fat bloom and re-crystallisation, while all other desirable properties, i.e. the presence of a steep SFC-profile, an interesting nutritional profile, i.e. a low content of trans fatty acids and a sufficiently low content of saturated fatty acids as well as a high crystallisation rate, are maintained.

5

10

15

20

25

30

The inventor has found that by incorporation of the fat composition obtainable with the process of this invention in the above described products, storage stability and shelf life may even be improved. Indeed, certain re-crystallisation and fat bloom phenomena can be retarded by several weeks or months, meaning an increased value for the final end product.

Another advantage of the current invention is that a higher amount of the low-trans first fat can be incorporated in the final fat composition as compared to the composition disclosed in PCT/BE02/00045, thus improving the economic feasibility of this fat.

A number of applications exist where the risk to the occurrence of fat re-crystallisation and bloom is rather high. This is mostly the case in recipes using a higher amount of cocoa-butter where the composition is not tempered and risks to re-crystallise, for example in confectionery coatings containing some cocoa mass besides defatted cocoa powder. The cocoa mass is added in order to increase the chocolate taste. This is also the case in recipes containing a higher amount of liquid oil where there is a risk to fat migration and re-crystallisation. An example of such recipe is a confectionery filling containing a high amount of nut paste, which contain a high amount of free liquid oil. The liquid oil acts as a transport medium for other fat components to migrate to the surface, where re-crystallisation can take place and visible crystals or crystals are formed, which during tasting are evaluated as a kind of graininess.

Furthermore, a fat composition showing the above described properties can be obtained without involving the need to use as a starting fat a fat component which has been subjected to expensive solvent fractionation processes and contains highly concentrated levels of POP or PPO triglycerides, to obtain a fat showing the optimum hardness for use in coatings or

hard centres or in confectionery products containing high amounts of liquid oils, for example with high amounts of hazelnut paste.

The fats obtainable with the present invention can be further distinguished from the known processes, in that they have an improved crystallisation rate, which is important as it determines the capacity of confectionery production lines and the energy needed to cool down and solidify end products before being packed.

The interesterified fat may be a single fat or a mixture of two or more interesterified fats.

10 In the present invention it is preferred to use an interesterified fat with a C-12 content of less than 3 wt. %, most preferably less than 1.5 wt. %. This means that it is preferred to use a non-lauric interesterified fat, in view of reducing the risk to the development of so-called soapy flavour. This is also done to reduce the risk to the occurrence of eutectic effects when using the fat composition in combination with non-lauric fats, in particular in applications

having a hard texture, for instance tablets or coatings.

Suitable interesterified fats for use with the starting fat of the present invention are fats containing palm or palm fractions. Examples of suitable fats include interesterified palm, interesterified palm stearin or olein, or mixtures containing of two or more of these products. These fats are non-lauric and their raw materials are widely available. Furthermore, as these fats contain an interesting amount of solid fat, the extent to which the starting fat needs to be hydrogenated to obtain the desired SFC-profile may be limited, as a consequence of which the risk to the building of trans fatty acids is limited.

When it is desired to increase the sharpness of the SFC-profile and to further improve the mouth feel of the product, the first fat may be subjected to a further fractionation, after the hydrogenation reaction has been

terminated. This can be particularly useful when producing fats for application in coatings and tablets, as fractionation allows increasing snap and reducing

waxiness.

5

15

20

25

30

In a preferred embodiment of the process for producing a fat with a sharp SFC-profile and a particularly low TFA-content, use is made of a starting fat composition containing an amount of a fractionated interesterified fat, in particular a fat that has been fractionated after interesterification. The amount of this fractionated fat incorporated into the starting fat composition will mostly range from 10 to 100 wt. % expressed on the total amount of interesterified fat present in the starting fat composition. The hydrogenation is carried out in such a way that the first fat obtained contains less than 8 wt. %, preferably less than 6.5 wt. %, most preferably less than 5 wt. % of trans fatty acids. Fractionation removes the fat components having a too high and too low melting point and in that way renders the SFC profile steeper. This steeper effect could also be obtained through hydrogenation, hydrogenation however entailing the risk to an increased content of trans fatty acids.

10

15

5

The first fat obtained with the above described process can be mixed with another fat, having a sharp SFC profile and a low trans fatty acid (TFA) content, so as to obtain a final fat composition with a TFA-content of less than 8 wt. %, preferably less than 6.5 wt. %, most preferably less than 5 wt. %. The second fat can for instance be a fat prepared according to PCT/BE02/00045. It was found that the thus obtained fat compositions show a steep SFC-profile which is particularly useful for confectionery coatings, a low TFA-content and a very good stability without necessitating tempering. These fat compositions can be obtained without necessitating the use of a highly fractionated and expensive fat composition containing over 70 wt. % of POP in view of providing the desired SFC profile.

20

The first fat obtainable with the process of this invention is preferably characterised by an SFC at 20°C of at least 35 wt. %, preferably at least 50 wt. %, most preferably at least 60 wt. %. High SFC's at 20°C are particularly desirable when using the first fat as such in tablets or coatings but also in fillings or creams containing a high amount of liquid oil where it is preferred that the first fat has a sufficiently high solid fat content so as to obtain a filling having a sufficiently hard texture.

30

25

The first fat is preferably a non temper fat. When using this fat either pure, in combination with other non-temper fats or in combination with a limited amount of temper type fat, stable products can be made without necessitating a tempering step in the manufacturing process, which is an important simplification.

In view of the envisaged properties of the end product, the man skilled in the art may use a fat composition obtainable with the above described method containing exclusively the first fat, or in other words containing 100 wt. % of the first fat. However, the man skilled in the art may as well blend the first fat with an amount of a second fat. Thereto, 10-100 wt. % of the first fat may be blended with 90-0 wt. % of a second fat. The second fat preferably has a C-12 content of less than 5 wt. %, most preferably less than 3 wt. %. To limit this C-12 content, the second fat is preferably substantially free of lauric components.

10

5

The second fat preferably contains an amount of a hydrogenated fat or an interesterified fat as these will generally show a good compatibility with the first fat.

To limit the trans fatty acid content of the final fat composition when using a mixture of the first fat with a second fat, it is preferred to use as a second fat a fat having a limited trans fatty acid content. In particular it is preferred that the second fat contains less than 15 wt. %, preferably less than 10 wt. %, most preferably less than 7.5 wt. % of trans fatty acids.

20

15

Very suitable fats for use as second fat are fats containing 70 wt. % or more of palm oil or palm oil fractions, or a mixture thereof. Examples of such fats are hydrogenated palm or hydrogenated palm olein, interesterified palm, interesterified palm oil fractions, which may be further fractionated after interesterification or hydrogenation or not, as these are fats with sufficient solid parts to give enough structure to the final fat composition, without giving high trans fatty acid levels.

25

An additional advantage of the fats obtainable with the present invention is their high crystallisation rate. This is an important parameter since it is linked to the capacity of confectionery production lines and the energy needed to cool down and solidify the products before being packed. Fat compositions obtainable with this process are characterised by a crystallisation time at 15°C of less than 15', preferably less than 10' to reach 50% of the SFC measured at 15°C according to IUPAC method 2.150a.

30

The present invention further relates to the use of fat compositions obtainable with the above described process, and the use of the above described fat compositions in the preparation of confectionery products.

The invention also relates to confectionery products containing the fat composition obtainable with the above described process, or containing a fat composition as described above. In particular it concerns confectionery products belonging to the group of fillings, creams, hard centres or caramel, or products like confectionery coatings or tablets.

The present invention is further elucidated in the examples and comparative examples given below.

Examples

10

15

5

Comparative example A.

A palm oil was dry fractionated so as to obtain a palm mid fraction (PMF) with an IV of 42. Other characteristics of this PMF are given in table 1. The thus obtained PMF was subjected to a catalytic hydrogenation, in the presence of a Ni catalyst type Pricat 9910 until a product was obtained with the characteristics of sample 1 summarised in table 1.

Table 1.

Product	PMF	Sample 1	
IA	42,0	38,6	
FAC	,•	23,2	
C12	0,26	0,28	
C14 .	1,01	1,05	
C16	50,25	50,23	
C18	5,14	5,66	
C18-1	37,19	40,19	
C18-2	5,11	1,86	
C18-3	0,00	0,00	
C 20	0,43	0,37	
TFA	0,71	7,71	~
SFA	57,21	57,71	
TFA+SFA	57,92	65,42	
Triglycerides		•	
S2U	69,51		
SU2+U3	18,57		
S3	1,29		
Diglycerides	8,85		
SFC			
10°C	76,9	88,9	
20°C	46,5	[:] 71,1	
25°C	8,4	49,1	
30°C	0,0	25,3	•
35°C	0,0	11,3	

5

15

Example 1.

A fat composition was prepared by

- (1) In a first step, mixing 60 wt. % of a PMF of comparative example A with 40 wt. % of random interesterified palm
- 10 (2) followed by a second step of subjecting this mixture to a catalytic hydrogenation, using a catalyst type Pricat 9910 (available from Synetix), a non-trans specific Ni catalyst.

The hydrogenation was continued until a product was obtained having the characteristics given in table 2, sample 2. The characteristics of the composition before hydrogenation are given in table 2 as Initial Fat Composition.

The Initial Fat Composition was too soft to be fit for use in confectionery coatings or filling recipes containing high amounts of liquid oil, and had a too slow crystallisation rate. As will become apparent from the examples given below, the problem of the too slow crystallisation rate can be overcome by subjecting the Initial Fat Composition to a slight hydrogenation, during which only a limited amount of TFA is built and the amount of saturated fatty acids is increased to only a minor extent. A particular advantage of the Initial Fat Composition is that it does not require the use of expensive fractionation processes, e.g. wet fractionation to render it suitable for use in confectionery products.

5

Table 2.

Product	Initial Fat	Sample 2	Sample 3
	Composition		Oumple 3
IV	46,6	40,2	43,4
FAC		.0,2	. 40,4
C12	0,48	0,55	0,32
C14	1,24	1,34	1,03
C16	49,35	50,30	
C18	4,49	4,89	43,04
C18-1	36,09	40,95	6,07
C18-2	7,41	1,13	47,53
C18-3	0,03	0,00	. 1,09
C 20	0,39	0,28	0
TFA	0,94	· 8,38	0,38 14,51
SFA	56,06	57,47	<u>-</u>
TFA+SFA	57,0	65,85.	50,94
Triglycerides	, -	00,00	65,45
S2U	56,58		
SU2+U3	29,59		
S3	4,92		•
Diglycerides	8,58		
SFC	-,		
10°C	69,0	87,5	96.0
15°C	57,7	78,6	86,0
20°C	39,3	65,4	76,4
25°C	18,2	45,9	62,8
30°C	8,2	27,1	46,3
35°C	3,5	14,3	29,7
Crystallisation ra	te at 15°C (*)	17,0	16,6
2,5 minutes	18,5%	·30,1%	40.5%
minutes	20,4%	47,3%	42,5%
7,5 minutes	21,1%	60,1%	61,8%
0 minutes	23,6%	68,7%	71,1%
5 minutes	36,0%	79,1%	75,9%
	,-,-	1 3,1 70	81,8%

^(*) SFC measured after a certain crystallisation time expressed as % of the SFC at 15°C measured according to IUPAC method 2.150a. The starting fat is completely molten at 80°C and is then put in a water bath at 15°C. From there on time registration starts.

Example 2.

A sample (sample 3) was prepared by blending 50 wt. % of a first fat, obtained by hydrogenating the Initial Fat Composition of Example 1, with a catalyst type Pricat 9910 to an IV of 39.1, with 50 wt. % of a second fat.

The second fat was obtained by hydrogenating a single fractionated palm olein, with an IV value of 56.6 in the presence of a catalyst type Pricat 9910, until a product was obtained with an IV of 48.1.

The characteristics of sample 3 are given in table 2.

10

15

20

5

Example 3.

Confectionery coatings were prepared using the fat composition of respectively comparative sample 1, and sample 2 and sample 3 according to the invention.

The recipe used for preparing these coatings is summarised in table 3. The coatings were prepared by first melting the fat composition of the comparative example, sample 2 or sample 3 and adding 1 wt. % of sorbitan tristearate. All ingredients, except part of the fat, were mixed and roll refined. After roll refining the mixed ingredients were further homogenised with the rest of the fat in a mixer with heated jacket at a temperature of 40°C.

Table 3.

Coating Recipe	%
Fat	29,2
Sugar	44,7
Cocoapowder 10/12	20,6
Cocoa Mass	. 5,1
Lecithine	0,4
Vanilline	0,05
Cocoa butter on total fat	14,8

With this coating mixture, tablets were moulded at a temperature of 45°C, whereafter the tablets were cooled for 30' at 5°C and thereafter for 30' at 15°C, following which the tablets were de-moulded. No tempering was applied. The tablets were stored in an incubator for 1 week at 20°C.

The bloom resistance of the tablets was tested by storing in incubators at different temperatures. Thereto, a first incubator was cycled in cycles of 12 hours between a temperature of respectively 15-25 °C, a second incubator was left at a temperature of 25 °C, a third one was maintained at a constant temperature of 28°C.

The results of these bloom tests are given in table 4. Scores are given from "no", indicating "no bloom" to "++++", indicating very "strong blooming"

From the results given in table 4 it can be seen that coatings containing an important amount of cocoa-butter, tend to bloom earlier when containing a fat composition of the type of sample 1 as compared to fats of samples 2 and 3. Samples 2 and 3 are both fats which contain an amount of an interesterified fat and are produced according to the process of the present invention, with the objective of improving bloom resistance.

5

10

15

20

Table 4.

Weeks		15-25 °C		Γ	25 °C			00.00	
	sample 1	sample 2	sample 3	sample 1	sample 2			28 °C	
1	no	no	no			sample 3	sample 1	sample 2	sample 3
2	+/-			no	no	no	no	no	no
3	1	no	no	+/-	no	no	+/-	no	no
	++	+ -	+/-	+	no .	no	+/-	no	no
4	++	+	+	++	no	no	+	no	_
5	++	+	+	++	no	no	· +		no
6	+++	++	++	+++	no	по		no	no
7	111	++	++	+++	no		++	no	no
8	44,1	++	+++			no	++	no	no
. 9	+++		i	+++	no	no	++	no	по
10		++	+++	+++	no	no	++	no	no
	+1-1	++	+++	+++	no	no	++	no	no
12	- +++	++	+++	+++	no	no	++	no	
. 14	+++	++	+++	++++	no	no			no
16	1111	+++	++++	+++	no	+/-	++	no	no
18	++++	++++	++++	+++			. ++	no	no
20	1111	1111			no	+	++	no	no
		<u> </u>	++++	+++	no	+	++	no	по

Example 4.

The samples of example 3 were used to prepare a filling containing a high amount of liquid oil, originating from hazelnut paste. The recipe of the filling is given in table 5.

Table 5.

Filling Recipe	%
Fat	23 [·]
Sugar	40
Cocoa Mass	5
Hazelnut paste	25
Skimmed milk powder	6,6
Lecithine	0,4
Vanilline	0,05

10

5

The fillings were prepared as follows: all ingredients, except the fat were mixed and roll refined. Thereafter, the mixture was further homogenised with the molten fat in a mixer with heated jacket at a temperature of 40°C. After homogenisation the mass was cooled to 35°C and poured into aluminium cups with a diameter of 28 mm and a height of 20 mm. The thus obtained fillings were cooled for 30' at 5°C, followed by 30' at 15°C.

20

25

15

The fillings were then stored at 20°C and weekly checked on the appearance of crystals at the surface, which would indicate migration of a fat component or re-crystallisation. The results of this test are given in table 6. In this table 6 "no" indicates no crystals at the surface, "+" means visible crystals at the surface.

From the results given in table 6 it can be concluded that samples 2 and 3 show a better resistance against migration and recrystallisation as compared to the comparative example sample nr 1.

Table 6.

Week	sample 1	sample 2	sample 3
1	no	no	no
2	no	no	no
3	no	no	no
4	no	no	no
5	no	no	no
6	+	no	no
7	+	no	no
8	+	no	no
9	+	no	no
10	+	no .	no
12	+	no	no
14	+	no	no
16	+	no	no

5

Example 5.

A fat A was prepared by hydrogenation of the PMF of comparative example A with an IV of 42.0 and a POP-content of 40.9 %, using a catalyst Pricat 9910, until a product was obtained with IV of 40.1 and a fatty acid composition as described in table 7.

A fat B was prepared by first interesterifying a palm oil followed by fractionation until a fat was obtained with IV 44.1 and a composition described in table 7 as "initial fat B", and then hydrogenating this fat, using a catalyst Pricat 9910, until a product was obtained with IV of 37.6 and a fatty acid composition as described in table 7. Initial fat B had a PPO content of 26.9 wt. %.

15

10

A coating fat sample (sample 4) was then prepared by combining 60% of fat A and 40% of fat B. This sample 4 had characteristics described in table 7. As can be seen the TFA content of sample 4 is very limited (6.69%) while the SFC-profile is steeper than for example fat sample nr 2. Sample 4 is also characterised by a quick crystallisation rate as can be seen from table 7.

20

The solid fat content (SFC) of sample 4 was measured at 30°C according to IUPAC method 2.150a (non-stabilised) and IUPAC method 2.150b (stabilised). The ratio between the 2 SFC results was only 1.24, indicating that fat sample 4 can be used in applications without a tempering step being necessary.

table 7

Product	Initial fat A	Fat A	Initial fat B	Fat B	Sample 4
IV ·	42,0	40,1	44,1	37,6	39,1
FAC				0.,0	00,1
C12	0,26	0,33	0,44	0,38 "	0,35
C14	1,01	1,13	1,10	1,16	1,14
C16	50,25	50,50	50,87	50,68	50,57
C18	5,14	5;30	5,14	5,38	5,33
C18-1	37,19	39,65	34,24	39,95	39,77
C18-2	5,11	2,32	7,20	0,92	1,76
C18-3	0,00	0,00	0,00	, O	0
C 20	0,43	0,31	0,41	0,41	0,35
TFA	0,71	6,58	0,91	6,86	6,69
SFA	57,21	57,57	57,96	58,00	57,74
TFA+SFA	57,92	64,15	58,87	64,85	64,43
Triglycerides				·	,
S2U	69,51		59,77		
SU2+U3	18,57		23,00		
S3	1,29		6,97		
Diglycerides SFC	8,85	•	5,39		
10°C					88,4
15°C .					79,5
20°C					67,6
25°C					46,5
30°C					24,4
35°C					10,9
Crystallisation	rate at 15°C				, .
2,5'					26,1%
5'					41,0%
7,5'					53,8%
10'			•	•	63,2%
15'					76,0%

Example 6.

A confectionery coating was prepared with fat nr 4, according to the recipe in table 3, using the same procedure as described in example 3.

Also here we added 1 % of sorbitan tristearate to the

fat.

Tablets were stored for 1 week at 20°C and then evaluated. The tablets were glossy and had good eating properties, meaning nice melting in the mouth without leaving a feeling of waxiness.

CLAIMS.

- 1. A process for the production of a fat composition,
 suitable for use as a confectionery fat, characterised in that a starting fat
 composition having the following glyceride composition:
 - a S_2U content of 30 80 wt. %, preferably 40 70 wt. %, most preferably 45 65 wt. %
 - a SU_2 + U_3 content less than 60 wt. %, preferably 10 50 wt. %, most preferably
- 10 20 40 wt. %,

15

20.

25

30

- a S_3 content less than 20 wt. %, preferably less than 15 wt. %, most preferably less than 10 wt. %
- a diglyceride content of 3 12 wt. %
- the starting fat composition containing between 10 and 100 wt. %, preferably 20 and 80 wt. %, most preferably between 30 and 70wt. % of an interesterified fat,

is subjected to a catalytic hydrogenation so as to obtain a first fat with a trans fatty acid content of less than 25 wt%, preferably less than 20 wt%, most preferably less than 10 wt%, and in that the first fat is incorporated in the fat composition, the glyceride content being expressed as wt. % with respect to the total amount of diand triglycerides, in which S means a saturated fatty acid with a hydrocarbon chain length of 14-24 carbon atoms, U means unsaturated fatty acid with a hydrocarbon chain length of 14-24 carbon atoms.

- A process according to claim 1, characterised in that the starting fat composition comprises palm oil or a fraction thereof.
 - 3. A process according to claim 1 or 2, characterised in that the interesterified fat contains less than 3 wt. %, preferably less than 1.5 wt. % of C12 fatty acid.
- 4. A process according to any one of claims 1 3, characterised in that the interesterified fat contains palm oil or a palm oil fraction.
- 5. A process according to any one of claims 1 4, characterised in that the first fat is subjected to a fractionation process after termination of the hydrogenation reaction.

6. A process according to any one of claims 1 - 5, characterised in that the interesterified fat contains an amount of fractionated interesterified fat which ranges between 10 and 100 wt. % with respect to the total amount of interesterified part, and in that the first fat obtained after hydrogenation contains less than 8 wt. %, preferably less than 6.5 wt. %, most preferably less than 5 wt. % of trans fatty acids.

5

10

15

20

25

30

7. A process according claim 6, characterised in that the first fat is incorporated in a fat composition, the fat composition having a trans fatty acid content of less than 8 wt. %, preferably less than 6.5 wt. %, most preferably less than 5 wt. %.

8. A process as claimed in any one of claims 1-7, characterised in that 10-100 wt. % of the first fat is mixed with 90-0 wt. % of a second fat, the second fat having a C12 fatty acid content of less than 5 wt. %, preferably less than 3 wt. %.

9. A fat composition obtainable with the method of any one of the claims 1-8, characterised in that the composition has an SFC at 20°C of at least 35 wt. %, preferably at least 50 wt. %, most preferably at least 60 wt. %.

10. A fat composition as claimed in claim 9, characterised in that the fat composition is a non-temper fat.

11. A fat composition as claimed in claim 9 or 10, characterised in that the composition contains 10-100 wt. % of the first fat and 90 – 0 wt. % of a second fat, the second fat having a C-12 fatty acid content of less than 5 wt. %, preferably less than 3 wt. %.

12. A fat composition as claimed in claim 11, characterised in that in that the second fat contains a hydrogenated or an interesterified fat.

13. A fat composition as claimed in claim 11 or 12, characterised in that in that the second fat contains less than 15 wt. %, preferably less than 10 wt. %, most preferably less than 7.5 wt. % of trans fatty acids.

14. A fat composition as claimed in any one of claims 11-13, characterised in that the second fat contains at least 70% wt. of palm oil, one or more palm oil fractions, interesterified palm oil, interesterified palm

oil fractions or one or more fractions of the afore mentioned fats or a mixture of two or more of the afore mentioned fats.

15. A fat composition as claimed in any one of claims 9-14, characterised in that the fat composition has a crystallisation time at 15°C of less than 15 minutes, preferably less than 10 minutes to reach 50% of its SFC measured at 15°C.

16. Use of the fat composition obtainable with the process of any one of claims 1-8 or a fat composition according to any one of claims 9 – 15 for the preparation of a confectionery product.

17. A confectionery product containing the fat composition obtainable with the process of any one of claims 1-8, or a fat composition according to any one of claims 9-15.

18. A confectionery product as claimed in claim 17, characterised in that the confectionery product is selected from the group of a filling, a cream, a hard centre or caramel.

19. A confectionery product as claimed in claim 17, characterised in that the confectionery product is a coating or a tablet.

15

5

ABSTRACT.

Low-trans fats for confectionery fat compositions.

The present invention relates to a process for the production of a fat composition, suitable for use as a confectionery fat. According to this invention a starting fat composition having the following glyceride composition:

- a S_2U content of 30 80 wt. %, preferably 40 70 wt. %, most preferably 45 65 wt. %
- a SU_2 + U_3 content less than 60 wt. %, preferably 10 50 wt. %, most preferably

20 - 40 wt. %,

5

10

20

- a S_3 content less than 20 wt. %, preferably less than 15 wt. %, most preferably less than 10 wt. %
- a diglyceride content of 3 12 wt. %
- the starting fat composition containing between 10 and 100 wt. %, preferably 20 and 80 wt. %, most preferably between 30 and 70wt. % of an interesterified fat.

is subjected to a catalytic hydrogenation so as to obtain a first fat with a trans fatty acid content of less than 25 wt%, preferably less than 20 wt%, most preferably less than 10 wt%. The thus obtained first fat is incorporated in the fat composition. The glyceride content is expressed as wt. % with respect to the total amount of diand triglycerides, S means a saturated fatty acid with a hydrocarbon chain length of 14-24 carbon atoms, U means unsaturated fatty acid with a hydrocarbon chain length of 14-24 carbon atoms.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.